

ALADINO STYLE



Ventilazione Frontale (1 Motore) - Uscita Fumi Posteriore - Uscita Fumi Superiore

Front Ventilation (1 Motor) - Rear Exhaust Fume Outlet - Ventilación Frontal (1 Motor) - Salida De Humos Trasera - Ventilation Avant (1 Moteur) - Sortie De Fumée Arrière - Front Gebläse (1 Motor) - Rauchausgang Hinten - Top Exhaust Fume Outlet - Salida De Humos Superior - Sortie De Fumée Supérieur - Rauchausgang Oben - Seitlicher Rauchausgang




Bordeaux
Bordeaux - Bordeaux
Bordeaux - Bordeaux

Blanco
White - Blanc - Blanco
- Weiß

Nero
Black - Noir - Negro -
Schwarz



TECHNOLOGY



OPTIONAL



Potenza Globale
Global Power
Puissance globale
Potencia global
Verbrennungsleistung

Rendimento totale
Total efficiency
Puissance globale
Potencia global
Pellet Wirkungsgrad

Peso
Weight
Poids
Gewicht

Consumo min-MAX
Min-Max consumption
Consumation min-MAX
Consumo min-maxi
Min-Maxi verbrauch

Temperatura gas di scarico
Exhaust gas temperature
Température des gaz d'échappement
Temperatura de los gases de escape
Abgas temperatur

Tracciato richiesto in funzionamento
Draw required in operation
Dessiner nécessaire en fonctionnement
Dibujar requerido en la operación
Erforderlicher Betriebszug

Uscita fumi
Chimney Output
Sortie conduit de cheminée
Salida conducto de humos
Rauchauslass

Ingresso aria
Air inlet
Entrée d'air
Entrada aire
Lufteinlass

Seratoio pellet
Pellet tank
Reservoir
Depósito
Tank Fassungsvermögen

Assorbimento elettrico watt
Electrical consumption watt
Absorption électrique watt
Consumo de electricidad watt
Elektrischer Verbrauch watt

A 13	KW 12,2-3,6	% 87,2	Kg 155	Kg/H 0,8-2,9	°C 232	Pa 3	mm 80	mm 60	Kg 21,0	M270-N93-R45
A 11	KW 11,0-3,6	% 87,6	Kg 155	Kg/H 0,8-2,6	°C 217	Pa 3	mm 80	mm 60	Kg 21,0	M270-N91-R45
A 9	KW 9,0-3,6	% 88,3	Kg 155	Kg/H 0,8-2,0	°C 189	Pa 3	mm 80	mm 60	Kg 21,0	M270-N89-R45

*Le Caldaie e le Stufe con sistema CLEAN svuotano il cassetto ceneri dopo un intero BANCALE di PELLET bruciato.

