

SLOT GLASS



Ventilazione Frontale (1 Motore) – Uscita Fumi Superiore
Front Ventilation (1 Motor) – Top Exhaust Fume Outlet – Ventilation Frontal
(1 Motor) – Salida De Humos Superior – Ventilation Avant (1 Moteur) – Sortie
De Fumée Supérieure – Front Gebläse (1 Motor) – Rauchausgang Oben

TECHNOLOGY

PELLET

CRONO

FIRE CONTROL SYSTEM

FIREWALL

RADIO

DOUBLE DOOR

FRONTAL GLASS

ROOM THERMOSTAT

SLIDE STOVES

SMOKE TOP

ECO DESIGN 2022

EMERGENCY DISPLAY

QUARTZ IGNITION

TRITTICO INOX

OPTIONAL

MORETTI DESIGN

WI-FI

DRAWER PELLET

	Potenza Globale Global Power Puissance globale Potencia global Verbrennungsleistung	Rendimento totale Total efficiency Puissance globale Potencia global Pellet Wirkungsgrad	Peso Weight Poids Gewicht	Consumo min-MAX Min-Max consumption Consumation min-MAX Consumo min-maxi Min-Maxi verbrauch	Temperatura gas di scarico Exhaust gas temperature température des gaz d'échappement temperatura de los gases de escape Abgastemperatur	Tiraggio richiesto in funzionamento Draw required in operation Dessiner necessaire en fonctionnement Dibujar requerido en la operación Erforderlicher Betriebszug	Uscita fumi Chimney Output Sortie conduit de cheminée Salida conducto de humos Rauchauslass	Ingresso aria Air inlet Entrée d'air Entrada aire Lufteinlass	Serbatoio pellet Pellet tank Reservoir Deposito Tank Fassungsvermögen	Assorbimento elettrico watt Electrical consumption watt Absorption électrique watt Consumo de electricidad watt Elektrischer Verbrauch watt
A 10	KW 10,4-3,1	% 90,8	Kg176	Kg/H 0,7-2,5	°C 166	Pa 10	mm 80	mm 60	Kg 12	W 100
A 8	KW 8,0-3,1	% 90,8	Kg176	Kg/H 0,7-2,0	°C 155	Pa 10	mm 80	mm 60	Kg 12	W 100

AIR LINE

