

ELEGANCE GLASS AQUA



Ventilazione Frontale - Uscita Fumi Posteriore
Front Ventilation - Rear Exhaust Fume Outlet - Ventilation Avant - Sortie
De Fumée Arrière - Ventilación Frontal - Salida De Humos Trasera - Front
Gebläse - Rauchausgang Hinten



TECHNOLOGY



OPTIONAL



	Potenza Globale Global Power Pissance globale Potencia global Verbrennungsleistung	Rendimento totale Total efficiency Pissance globale Potencia global Pellet Wirkungsgrad	Potenza all'acqua Water power Pissance à l'eau Potencia al agua Wärmeleistung wasserseitig	Potenza all'ambiente Power Environment Pissance à l'ambient Potencia al ambiente Raumwärmeleistung	Peso Weight Poids Gewicht	Consumo min-MAX Min-Max consumatio Consumation min-MAX Consumo min-maxi Min-Maxi verbrauch	Uscita fumi Chimney Output Sortie conduit de cheminée Salida conducto de humos Rauchauslass	Ingresso aria Air inlet Entrée d'air Entrada aire Lufteinlass	Serbaio pellet Pellet tank Réservoir Deposito Tank fassungsvermögen	Pressione d'esercizio Pressure Pression de service Presión de funcionamiento Betriebsdruck	Assorbimento elettrico watt Electrical consumption watt Absorption électrique watt Consumo de electricidad watt Elektrischer Verbrauch watt
AQUA 18 KW	KW 22,3-5,3	% 94,3	KW 17,5	KW 4,8	Kg 250	Kg/H 12-4,8	mm 80	mm 60	Kg 20	BAR 1,5	M395-N100-R26
AQUA 16 KW	KW 20,5-5,3	% 94,7	KW 16,0	KW 4,5	Kg 250	Kg/H 12-4,4	mm 80	mm 60	Kg 20	BAR 1,5	M395-N95-R26
AQUA 14 KW	KW 18,2-5,3	% 95,3	KW 14,0	KW 4,2	Kg 250	Kg/H 12-3,9	mm 80	mm 60	Kg 20	BAR 1,5	M395-N87-R26
AQUA 12 KW	KW 15,9-5,3	% 95,8	KW 12,0	KW 3,9	Kg 250	Kg/H 12-3,3	mm 80	mm 60	Kg 20	BAR 1,5	M395-N80-R26
AQUA 10 KW	KW 15,5-5,3	% 95,9	KW 11,7	KW 3,8	Kg 250	Kg/H 12-3,2	mm 80	mm 60	Kg 20	BAR 1,5	M395-N79-R26

*Le Caldaie e le Stufe con sistema **CLEAN** svuotano il cassetto ceneri dopo un intero **BANCALE** di **PELLET** bruciato.

